

## SAFETY DATA SHEET

#### 1. Identification

Product number

1000004842

Product identifier

STAINLESS STEEL POLISH & CLEANER (OIL BASE)

Company information

Claire Manufacturing Co. 1005 S. Westgate Drive

Addison, IL 60101 United States

Company phone

General Assistance 1-630-543-7600

Emergency telephone US Emergency telephone outside 1-866-836-8855

1-952-852-4646

Version #

01

Recommended use

**CLEANER** 

Recommended restrictions

None known.

## 2. Hazard(s) identification

Physical hazards

Flammable aerosols

Category 1

Health hazards

Serious eye damage/eye irritation

Category 2A

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Environmental hazards

Hazardous to the aquatic environment, acute

Category 3

hazard

Hazardous to the aquatic environment,

Category 3

long-term hazard

OSHA defined hazards

Not classified.

Label elements



Signal word

Danger

Hazard statement

Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear eye/face protection.

Response

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Product name: STAINLESS STEEL POLISH & CLEANER (OIL BASE) Product #: 1000004842 Version #: 01 Issue date: 01-19-2015

Chemical name Common name and synonyms		CAS number	%	
Distillates (Petroleum), Hydrotreated Light		64742-47-8	20 - 40	
White Mineral Oil		8042-47-5	20 - 40	
Acetone		67-64-1	10 - 20	
Propane		74-98-6	10 - 20	
Methyl Acetate		79-20-9	2.5 ~ 10	
Fragrance		Proprietary	0.1 - 1	
Odorless Mineral Spirits		64741-65-7	0.1 - 1	
D-Alpha Tocopherol (Vitamin E)		59-02-9	0.01 - 0.1	

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact

Wash off with soap and water, Get medical attention if irritation develops and persists.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth, Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire-fighting

equipment/instructions

Specific methods

General fire hazards

Powder, Alcohol resistant foam, Dry chemicals, Carbon dioxide (CO2),

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure, Pressurized container may explode when exposed to heat or flame.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes. Extremely flammable aerosol.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

#### Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 3 Aerosol.

Store locked up. Pressurized container, Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for A Components	Туре	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Methyl Acetate (CAS 79-20-9)	PEL	610 mg/m3	
·		200 ppm	
Propane (CAS 74-98-6)	PEL	. 1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Valu	es		
Components	Type	Value	
Acetone (CAS 67-64-1)	STEL	750 ppm	
	TWA	500 ppm	
Methyl Acetate (CAS 79-20-9)	STEL	250 ppm	
•	TWA	200 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Type	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Methyl Acetate (CAS 79-20-9)	STEL	760 mg/m3	
		250 ppm	
	TWA	610 mg/m3	
		200 ppm	
Propane (CAS 74-98-6)	Τ <b>WA</b>	1800 mg/m3	
		1000 ppm	
ogical limit values			

#### Bio

ACGIH Biological Exposure Indices					
Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

#### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Hand protection

Wear appropriate chemical resistant gloves.

Skin protection

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

Appearance

Clear.

Physical state

Gas. Aerosol.

Form

Light yellow.

Color Odor .

Citrus

Odor threshold

Not available.

Нq

Not available.

NE 545 1 41C ...

VUL avallable.

Melting point/freezing point

Not available.

Initial boiling point and boiling

62.28 °F (16.82 °C) estimated

range

Flash point

-156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

2.5 % estimated

(%)

Flammability limit - upper

12 % estimated

(%)

Explosive limit - lower (%)

Not available. Not available.

Explosive limit - upper (%)

45 - 65 psig @70F estimated

Vapor pressure

Not available.

Vapor density Relative density

Not available.

Solubility(ies)

Not available.

Solubility (water)

Not available.

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature

488.23 °F (253.46 °C) estimated

Decomposition temperature

Not available.

Viscosity

Not available.

Other information

Specific gravity

0.765 - 0.865 estimated

## 10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

Hazardous polymerization does not occur.

reactions

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Product name: STAINLESS STEEL POLISH & CLEANER (OIL BASE)

SDS US

Incompatible materials

Hazardous decomposition

Acids. Strong oxidizing agents. Nitrates.

products

No hazardous decomposition products are known.

## 11. Toxicological information

Information on likely routes of exposure

Ingestion

Not available.

Inhalation

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects. Prolonged

inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Causes serious eye irritation.

Symptoms related to the physical, chemical and

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

toxicological characteristics

Information on toxicological effects

Acute toxicity

Narcotic effects.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		•
LC50	Rat	55700 ppm, 3 Hours
	•	132 mg/l, 3 Hours
		50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Distillates (Petroleum), Hydr	otreated Light (CAS 64742-47-8)	
Acute	,	
Dermal	•	
LD50	Rabbit	> 2000 mg/kg
		> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 7.5 mg/l, 6 Hours
		> 4.6 mg/l, 4 Hours
Oral		
LD50	Rat ·	> 5000 mg/kg
Methyl Acetate (CAS 79-20-	-9)	
Acute		
Dermal	,	
LD50	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC100	Rabbit	98.4 mg/l, 4 Hours
Oral		
LD50	Rat	6482 mg/kg

Product name: STAINLESS STEEL POLISH & CLEANER (OIL BASE) Product #: 1000004842 Version #: 01 Issue date: 01-19-2015

Components	Species		Test Results
Propane (CAS 74-98-6)			
Acute			
Inhalation	34		1237 mg/l, 120 Minutes
LC50	Mouse		•
	•		52 %, 120 Minutes
	Rat		1355 mg/l
			658 mg/l/4h
White Mineral Oil (CAS 8042-47-5	5)		
Acute			
<i>Dermal</i> LD50	Rabbit		> 2000 mg/kg, 24 Hours
Inhalation	rassir		2000
LC50	Rat		2.18 mg/l, 4 Hours
Oral	, 151		· ·
LD50	Rat		5000,0001 mg/kg
8			
		litional component data not shown.	
Skin corrosion/irritation	_	in contact may cause temporary irritati	on.
Serious eye damage/eye irritation	Causes serio	us eye irritation.	
Respiratory or skin sensitizatio			
Respiratory sensitization	Not available.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product i	is not considered to be a carcinogen b	y IARC, ACGIH, NTP, or OSHA.
OSHA Specifically Regulate Not listed.	ed Substances	(29 CFR 1910.1001-1050)	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.		
Specific target organ toxicity - single exposure	May cause di	rowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Not classified	I.	
Aspiration hazard	Not available.		
Chronic effects	Prolonged inhalation may be harmful.		
12. Ecological information	n		
		quatic life with long lasting effects.	·
Ecotoxicity Product	i jaimai to ac	Species	Test Results
STAINLESS STEEL POLISH	LA CLEANER (C		TOT TO SETE
Aquatic	A OLEMALIN (	SIL BAGE) (ONG MIXIGIO)	
Algae	IC50	Algae	1283.3676 mg/L, 72 Hours estimated
Crustacea	EC50	Daphnia	8543,2627 mg/L, 48 Hours estimated
Fish	LC50	Fish	8.2044 mg/L, 96 Hours estimated
Components	2000	Species	Test Results
Acetone (CAS 67-64-1)		*	
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours

Test Results Species Components Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8) Aquatic 2.9 mg/l, 96 hours Rainbow trout, donaldson trout LC50 Fish (Oncorhynchus mykiss) Methyl Acetate (CAS 79-20-9) Aquatic 120,0001 mg/L, 72 Hours IC50 Algae Algae 1026.7 mg/L, 48 Hours Daphnia Crustacea **EC50** Fathead minnow (Pimephales promelas) 295 - 348 mg/l, 96 hours LC50 Fish Odorless Mineral Spirits (CAS 64741-65-7) Aquatic 30000 mg/L, 72 Hours IC50 Algae Algae White Mineral Oil (CAS 8042-47-5) Aquatic 10000.0001, 96 Hours Fish LC50 Fish \* Estimates for product may be based on additional component data not shown. No data is available on the degradability of this product. Persistence and degradability No data available. Partition coefficient n-octanol / water (log Kow) -0.24

Bioaccumulative potential

Acetone Methyl Acetate Propane

0.18 2.36

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

## US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1)

U002

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

## 14. Transport information

DOT

UN number

UN1950

UN proper shipping name

Aerosols, flammable

Transport hazard class(es)

2.1 Class Subsidiary risk 2.1 Label(s)

Not applicable. Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions

Packaging exceptions

306

Packaging non bulk

None

Packaging bulk

None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

UN number

UN1950

UN proper shipping name

Aerosols, flammable

Transport hazard class(es)

Class

2.1

Subsidiary risk Label(s)

2.1

Packing group

Not applicable.

Environmental hazards

No.

**ERG** Code

10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed.

aircraft

Allowed.

Cargo aircraft only **Packaging Exceptions** 

LTD QTY

**IMDG** 

UN number

UN1950

UN proper shipping name

**AEROSOLS** 

Transport hazard class(es)

Class

2.1

Subsidiary risk

Label(s)

2,1

Packing group

Not applicable.

Not applicable.

Environmental hazards

Marine pollutant

No.

**EmS** 

F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** 

LTD QTY

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

DOT





General information

IMDG Regulated Marine Pollutant.

## 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed.

SARA 304 Emergency release notification

Not regulated.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

# Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)

6532

#### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)

35 %WV

## **DEA Exempt Chemical Mixtures Code Number**

Acetone (CAS 67-64-1)

6532

### US state regulations

#### US, Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Methyl Acetate (CAS 79-20-9)

Propane (CAS 74-98-6)

## US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Methyl Acetate (CAS 79-20-9) Propane (CAS 74-98-6)

## US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Methyl Acetate (CAS 79-20-9)

Propane (CAS 74-98-6)

#### US. Rhode Island RTK

Acetone (CAS 67-64-1)

Propane (CAS 74-98-6)

#### US, California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	. Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan .	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date

01-19-2015

Version #

01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Product name: STAINLESS STEEL POLISH & CLEANER (OIL BASE)
Product #: 1000004842 Version #: 01 Issue date: 01-19-2015